



COR VISION PLUS SLIDING SYSTEM

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w \geq 0.9$ (W/m²K)

Please consult typology, dimensions and glazing

ACCOUSTIC INSULATION

Maximum glazing: **54 mm**

Maximum acoustic insulation: **Rw = 43 dB**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 4

Water tightness (EN 12208):

Class 7A* / 9A*

Wind resistance (EN 12210):

Class C3* / C4**

* Reference test balcony 4.00 x 3.00 m / 2 sashes

** Reference test balcony 4.00 x 3.00 m / 1 sash + 1 fixed light

SECTIONS	Frame 180 mm / 278 mm 3 Rails Sash 69 mm	EXTRUSION ALLOY	6063 T-5
PROFILE THICKNESS	Door 2.0 mm	POLYAMIDE STRIP LENGTH	Frame 40 mm Sash 18 / 32 mm
MAXIMUM DIMENSIONS	Width (L) = 4.000 mm Height (H) = 4.0000 mm <small>*Glazed surface 14 m</small>	OPENING POSSIBILITIES	Sliding 1, 2, 3, and 4 sashes Possibility of interior and exterior corner sash at 90° without mullion Galandage
MAXIMUM WEIGHT/SASH	400 kg Manual 700 Kg Motorized		

Please consult regarding maximum weight and dimensions according to types

FINISHES

Colour powder coating
(RAL, mottled, rough...)

According to Qualicoat >60 micras

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

